


EZ15983

NITY ZRYWALNE ŁEB PŁASKI

Blindrivets with break mandrel

PN-EN ISO 15983



d	l	dk	k _{max}	zakres łączenia	moment ścianania	moment rozciąg.	asort. w ofercie	
[mm]	[mm]	[mm]	[mm]	[mm]	[N]	[N]		[szt./pc.]
2,4	4	5	0,55	0,5-2,0	1000	1500	●▲	500
	6	5	0,55	2,0-4,0	1000	1500	●▲	500
	8	5	0,55	4,0-6,0	1000	1500	●▲	500
3	6	6,3	1,3	0,5-3,0	1800	2200	●▲	500
	8	6,3	1,3	3,0-5,0	1800	2200	●▲	500
	10	6,3	1,3	5,0-6,5	1800	2200	●▲	500
	12	6,3	1,3	6,5-8,5	1800	2200	●▲	500
	14	6,3	1,3	8,5-10,5	1800	2200	●▲	500
	16	6,3	1,3	10,5-12,5	1800	2200	●▲	500
3,2	6	6,7	1,3	0,5-3,0	1900	2500	●▲	500
	8	6,7	1,3	3,0-5,0	1900	2500	●▲	500
	10	6,7	1,3	5,0-6,5	1900	2500	●▲	500
	12	6,7	1,3	6,5-8,5	1900	2500	●▲	500
	14	6,7	1,3	8,5-10,5	1900	2500	●▲	500
	16	6,7	1,3	10,5-12,5	1900	2500	●▲	500
	18	6,7	1,3	12,0-14,0	1900	2500	●▲	500
4	6	8,4	1,7	1,0-2,5	2700	3500	●▲	500
	8	8,4	1,7	2,5-4,5	2700	3500	●▲	500
	10	8,4	1,7	4,5-6,5	2700	3500	●▲	500
	12	8,4	1,7	6,5-8,5	2700	3500	●▲	500
	14	8,4	1,7	8,5-10,0	2700	3500	●▲	500
	16	8,4	1,7	10,0-12,0	2700	3500	●▲	500
	18	8,4	1,7	12,0-14,0	2700	3500	●▲	500
	20	8,4	1,7	14,0-16,0	2700	3500	●▲	500
	25	8,4	1,7	16,0-21,0	2700	3500	●▲	500
4,8	6	10,1	2	1,5-2,0	4000	5000	●▲	500
	8	10,1	2	2,0-4,0	4000	5000	●▲	500
	10	10,1	2	4,0-6,0	4000	5000	●▲	500
	12	10,1	2	6,0-8,0	4000	5000	●▲	500
	14	10,1	2	8,0-9,5	4000	5000	●▲	500
	16	10,1	2	8,0-11,0	4000	5000	●▲	500
	18	10,1	2	11,0-13,0	4000	5000	●▲	500
	20	10,1	2	13,0-16,0	4000	5000	●▲	250
	22	10,1	2	15,0-17,0	4000	5000	●▲	250
	24	10,1	2	16,0-18,0	4000	5000	●▲	250
	25	10,1	2	16,0-19,0	4000	5000	●▲	250
	26	10,1	2	18,0-20,0	4000	5000	●▲	250
	30	10,1	2	21,0-25,0	4000	5000	●▲	250

d	l	dk	k _{max}	zakres łączenia	moment ścianania	moment rozciąg.	asort. w ofercie	
[mm]	[mm]	[mm]	[mm]	[mm]	[N]	[N]		[szt./pc.]
	35	10,1	2	25,0-30,0	4000	5000	●▲	250
	40	10,1	2	30,0-34,0	4000	5000	●▲	250
5	8	10,5	2,1	2,0-4,0	4700	5800	●▲	250
	10	10,5	2,1	4,0-6,0	4700	5800	●▲	250
	12	10,5	2,1	6,0-8,0	4700	5800	●▲	250
	14	10,5	2,1	8,0-9,5	4700	5800	●▲	250
	16	10,5	2,1	8,0-11,0	4700	5800	●▲	250
	18	10,5	2,1	11,0-13,0	4700	5800	●▲	250
	20	10,5	2,1	13,0-16,0	4700	5800	●▲	250
	22	10,5	2,1	15,0-17,0	4700	5800	●▲	250
	24	10,5	2,1	16,0-18,0	4700	5800	●▲	250
	25	10,5	2,1	16,0-19,0	4700	5800	●▲	250
	26	10,5	2,1	18,0-20,0	4700	5800	●▲	250
	30	10,5	2,1	20,0-25,0	4700	5800	●▲	250
	35	10,5	2,1	25,0-30,0	4700	5800	●▲	250
	40	10,5	2,1	30,0-34,0	4700	5800	●▲	250
6	8	12	2,5	2,0-4,0	5700	7500	●▲	250
	10	12	2,5	4,0-6,0	5700	7500	●▲	250
	12	12	2,5	6,0-8,0	5700	7500	●▲	250
	14	12	2,5	7,0-9,5	5700	7500	●▲	250
	16	12	2,5	8,0-11,0	5700	7500	●▲	250
	18	12	2,5	9,0-13,0	5700	7500	●▲	250
	20	12	2,5	11,0-15,0	5700	7500	●▲	250
	25	12	2,5	15,0-20,0	5700	7500	●▲	250
	30	12	2,5	20,0-24,0	5700	7500	●▲	250
	35	12	2,5	24,0-29,0	5700	7500	●▲	250
	40	12	2,5	29,0-34,0	5700	7500	●▲	250
6,4	10	13	2,6	2,0-4,0	6500	8850	●▲	250
	12	13	2,6	4,0-6,0	6500	8850	●▲	250
	14	13	2,6	6,0-8,0	6500	8850	●▲	250
	16	13	2,6	7,0-10,0	6500	8850	●▲	250
	18	13	2,6	9,0-13,0	6500	8850	●▲	250
	20	13	2,6	13,0-16,0	6500	8850	●▲	250
	22	13	2,6	14,0-17,0	6500	8850	●▲	250
	25	13	2,6	15,0-19,0	6500	8850	●▲	250
	30	13	2,6	19,0-23,0	6500	8850	●▲	250
	35	13	2,6	23,0-28,0	6500	8850	●▲	250
	40	13	2,6	28,0-33,0	6500	8850	●▲	250

● - asortyment A2 w ofercie / product A2 in offer | ▲ - asortyment A4 w ofercie / product A4 in offer