
LS502 Dowel drill bits with HM finishing - left









Features - benefits

- shank/bit made from high-alloy tool steel
- tips from the highest quality sintered carbide
- cylindrical shank with flattening for easier installation in the holder
- standard drills produced with 2 spirals- to order drills with 4 spirals
- offer includes drill bits with total length of 77mm, 85mm, 90mm, 105mm and drill bits from full carbide

Application

- drilling of blind holes for dowels, fasteners and fittings in plastics, wood-based materials and wood
- drilling of blind holes in wood window profiles and doors
- drills used on multi-spindle drilling machines and CNC machining centers

Catalogue	Index	∅ D [mm] Working diameter	S [mm] Shank diameter	H1 [mm] Working length	H [mm] Total length	R/L prawy=Right/lewy=Left	U.m.
●	LS502-0410-0001	4	10	35	57,5	lewy	szt.
●	LS502-0510-0001	5	10	35	57,5	lewy	szt.
●	LS502-0610-0001	6	10	35	57,5	lewy	szt.
○	LS502-0710-0001	7	10	35	57,5	lewy	szt.
●	LS502-0810-0001	8	10	35	57,5	lewy	szt.
○	LS502-0910-0001	9	10	35	57,5	lewy	szt.
●	LS502-1010-0001	10	10	35	57,5	lewy	szt.
○	LS502-1110-0001	11	10	35	57,5	lewy	szt.
●	LS502-1210-0001	12	10	35	57,5	lewy	szt.
●	LS502-0410-0002	4	10	50	70	lewy	szt.
●	LS502-0510-0002	5	10	50	70	lewy	szt.
●	LS502-0610-0002	6	10	50	70	lewy	szt.
○	LS502-0710-0002	7	10	50	70	lewy	szt.
●	LS502-0810-0002	8	10	50	70	lewy	szt.
○	LS502-0910-0002	9	10	50	70	lewy	szt.
●	LS502-1010-0002	10	10	50	70	lewy	szt.
○	LS502-1110-0002	11	10	50	70	lewy	szt.
●	LS502-1210-0002	12	10	50	70	lewy	szt.

Download

TechInfo_CL_LJ_eng.pdf

Related products

Dowel drill bits with HM finishing - right



Through hole drill bits with HM finishing - right



Through hole drill bits with HM finishing - left



HM cylinder boring bits



GOLD shank drill bits for hinges and hinge cups

