


LS504

Through hole drill bits with HM finishing - left



Features - benefits

- » shank/bit made from high-alloy tool steel
- » tips from the highest quality sintered carbide
- » cylindrical shank with flattening for easier installation in the holder
- » standard drills produced with 2 spirals- to order drills with 4 spirals
- » offer includes drill bits with total length of 77mm, 85mm, 90mm, 105mm and drill bits from full carbide

Application

- » drilling of through holes for dowels, fasteners and fittings in plastics, wood-based materials and wood
- » drilling of through holes in wood window profiles and doors
- » drills used on multi-spindle drilling machines and CNC machining centers

Catalogue	Index	Ø D [mm] Working diameter	S [mm] Shank diameter	H1 [mm] Working length	H [mm] Total length	R/L prawy=Right/lew y=Left	U.m.
●	LS504-0510-0001	5	10	35	57,5	lew	szt.
●	LS504-0610-0001	6	10	35	57,5	lew	szt.
●	LS504-0810-0001	8	10	35	57,5	lew	szt.
●	LS504-0410-0001	4	10	50	70	lew	szt.
●	LS504-0510-0002	5	10	50	70	lew	szt.
●	LS504-0610-0002	6	10	50	70	lew	szt.
○	LS504-0710-0001	7	10	50	70	lew	szt.
●	LS504-0810-0002	8	10	50	70	lew	szt.
○	LS504-0910-0001	9	10	50	70	lew	szt.
●	LS504-1010-0001	10	10	50	70	lew	szt.
○	LS504-1110-0001	11	10	50	70	lew	szt.
●	LS504-1210-0001	12	10	50	70	lew	szt.

Download

[TechInfo_CL_UJ_eng.pdf](#)

Related products

[Dowel drill bits with HM finishing - right](#)
[Dowel drill bits with HM finishing - left](#)
[Through hole drill bits with HM finishing - right](#)
[HM cylinder boring bits](#)



[GOLD shank drill bits for hinges and hinge cups](#)

