
# LS550 HM cylinder boring bits









## Features - benefits

- tips from the highest quality sintered carbide ? longer tool life time
- shank/bit made from high-alloy tool steel with high impact strength and cracking resistance
- cylindrical shank with flattening for easier installation in the holder
- offer includes drill bits with total length of 90mm, 105mm, 110mm and 120mm

## Application

- drilling of blind holes in wood window profiles and doors eg. for hinges, handles
- ideal solution for drilling in wood and wood-based materials
- drills used on multi-spindle drilling machines and CNC machining centers

| Catalogue | Index | ∅ D [mm] Working diameter | S [mm] Shank diameter | H1 [mm] Working length | H [mm] Total length | R/L prawy=Right/lewy=Left | U.m. |
|---|---|---|---|---|---|---|---|
| ○ | LS550-1510-0003 | 15 | 10 | 15 | 57 | prawy | szt. |
| ○ | LS550-1510-0004 | 15 | 10 | 15 | 70 | prawy | szt. |
| ○ | LS550-1510-0005 | 15 | 10 | 15 | 57 | lewy | szt. |
| ○ | LS550-1510-0006 | 15 | 10 | 15 | 70 | lewy | szt. |
| ○ | LS550-2010-0001 | 20 | 10 | 15 | 57 | prawy | szt. |
| ○ | LS550-2010-0002 | 20 | 10 | 15 | 70 | prawy | szt. |
| ○ | LS550-2010-0006 | 20 | 10 | 15 | 57 | lewy | szt. |
| ○ | LS550-2010-0003 | 20 | 10 | 15 | 70 | lewy | szt. |
| ○ | LS550-2510-0001 | 25 | 10 | 15 | 57 | prawy | szt. |
| ○ | LS550-2510-0002 | 25 | 10 | 15 | 70 | prawy | szt. |
| ○ | LS550-3010-0006 | 30 | 10 | 15 | 70 | prawy | szt. |
| ○ | LS550-3510-0002 | 35 | 10 | 15 | 70 | prawy | szt. |
| ○ | LS550-3510-0001 | 35 | 10 | 15 | 57 | prawy | szt. |

## Download

TechInfo_CL_LJ_eng.pdf

## Related products

Dowel drill bits with HM finishing - right

Dowel drill bits with HM finishing - left

Through hole drill bits with HM finishing - right

Through hole drill bits with HM finishing - left






GOLD shank drill bits for hinges and hinge cups

