



DI500

Cylinder boring bits DIA



Features - benefits

- » special steel body
- » PCD tip height 2,5mm enables: 3 - 4 sharpenings
- » configuration and construction of cutting edge guarantee the highest quality and efficiency measured in thousand of drillings

Application

- » used in multi spindle drilling machines or stationary drilling machines or CNC machining centre
- » PCD drill bits designed for processing OF chipboard with laminate, foil or raw chipboard and MDF

Catalogue	Index	Ø D [mm] Working diameter	S [mm] Shank diameter	H [mm] Total length	Z Edge number	H PCD [mm] Knife height PCD	U.m.
○	DI500-1510-0001	15	10	57	2+2	2,5	szt.
○	DI500-2510-0001	25	10	57	2+2	2,5	szt.
○	DI500-2610-0001	26	10	57	2+2	2,5	szt.
○	DI500-3010-0001	30	10	57	2+2	2,5	szt.
○	DI500-3510-0001	35	10	57	2+2	2,5	szt.
○	DI500-4010-0001	40	10	57	2+2	2,5	szt.
○	DI500-1510-0002	15	10	70	2+2	2,5	szt.
○	DI500-2510-0002	25	10	70	2+2	2,5	szt.
○	DI500-2610-0002	26	10	70	2+2	2,5	szt.
○	DI500-3010-0002	30	10	70	2+2	2,5	szt.
○	DI500-3510-0002	35	10	70	2+2	2,5	szt.
○	DI500-4010-0002	40	10	70	2+2	2,5	szt.

INFO:
cylinder boring bits made in versions: left and right

Download

[TechInfo_DI_eng.pdf](#)

Related products

[Clamps](#)

[Grips](#)

[GOLD shank drill bits for hinges and hinge cups](#)

