



PS342

Saw blades LL CUT VH line GŁ (HZ-DZ) for cutting veneered and laminated chipboards without scoring saw blade



Features - benefits

- » guarantee high cutting quality and a super clean exit from the material
- » perfect surface of ripping during processing of facing boards materials and materials covered with natural veneer
- » possibility of cutting a furniture board without the scoring saw blade
- » manufactured in the technology of industrial saws where deviations from the nominal dimensions are narrowed to hundredths of a millimeter, the bore of the tool with high quality and H7 tolerance
- » the SUPER HARD sintered carbide type NANOGRAIN with hardness over 2250 HV guarantees even longer satisfaction with the effects of the saw between successive sharpening
- » LL CUT VH line series with GŁ (HZ-DZ) teeth geometry ought to be sharpened only on the clearance surface of the sintered carbide (do not allow high blunting on the edge of the blade - radius larger than R 1mm)

Application

- » saw blades with specialist blade geometry GŁ10 (HZ-DZ) (positive) and GŁ-5 (HZ-DZ) (negative) with a concave (arched) tooth rake surface, dedicated for processing veneered and laminated chipboards
- » also dedicated for dry wood cutting (including exotic wood), natural veneer boards or facing boards
- » for cutting on horizontal (GŁ10) and vertical (GŁ-5) formatting machines, table saws and arm saws - the saws can work with a scoring saw blade
- » perfect for cutting countertops and other elements made of glued wood
- » wide spectrum of heights of cut materials (from 10mm to 100mm - depending on the saw diameter, among others)
- » possibility of using one saw for solid wood and wood-based materials while maintaining very good cutting quality
- » in order to extend the life of the saw it is required to sharpen it on specialized CNC grinders or sharpeners with intensive oil cooling

Catalogue	Index	Ø D [mm] Outer diameter	Ø d [mm] Inner diameter	B [mm] Kerf	S [mm] Disc thickness	Z Teeth number	Teeth geometry	Rake angle °	Silenced	ilxdo/dp Driver holes [mm]	U.m.
●	PS342-0250-0002	0250	30	3,2	2,2	80	GŁ	10	wyciszeni e_L	COMBO	szt.
●	PS342-0300-0001	0300	30	3,2	2,2	96	GŁ	10	wyciszeni e_L	COMBO	szt.
○	PS342-0250-0003	0250	30	3,2	2,2	80	GŁ	-5	wyciszeni e_L	COMBO	szt.
○	PS342-0303-0001	0303	30	3,2	2,2	96	GŁ	-5	wyciszeni e_L	COMBO	szt.

Legend:

- do - driving holes diameter
- dp - pitch diameter of holes
- silence slot L - type of silence slots

Download

[TechInfo_PS_eng.pdf](#)

Related products

[Saw blades LL CUT line GA5 / GA10 for cutting wood derived materials](#)

[Saw blades LL CUT VH line GA5 / GA10 for cutting wood derived materials](#)

[Saw blades LL CUT speedline GA15 for cutting wood derived materials](#)

[Saw blades FINISH CUT VH series for dry hard and exotic wood cutting](#)



[Saw blades LL CUT VH line 3GS for batch cutting frames and natural veneer materials](#)



[GO Cleaner - cleaning fluid for tools and machines](#)

