


EZ7504 M

## GLOTECH - Self-tapping screws with PH flat-lens head - DIN 7504 M

New



## Features - benefits

PH GLOTECH self-tapping screw with a flat-lens head, made from A2 (stainless steel) or A4 (acid-resistant steel)  
The screw is characterised by high strength and corrosion resistance  
Self-tapping screws with other technical specifications can be manufactured to order

## Application

ideal for joining light/soft metals, e.g. aluminium (not steel!!!)  
self-drilling screw with a Phillips head for use in damp environments  
also used for joining timber (particularly hardwood) and various wood-based materials  
Used in house construction (roofs, balustrades, aluminium structures, etc.) and in watercraft (ships, yachts, etc.)  
Suitable for assembling timber structures, cladding, decking, fences, etc.  
A screw used in many industries

| Catalogue | Index         | Ø d [mm]<br>Thread<br>diameter | l [mm]<br>Working<br>length of the<br>screw | Guide | Material grade         | Other<br>standard | Quantity per<br>pack | U.m.  |
|-----------|---------------|--------------------------------|---------------------------------------------|-------|------------------------|-------------------|----------------------|-------|
| ●         | EZ75042M35 13 | 3,5                            | 13                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M35 16 | 3,5                            | 16                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M35 19 | 3,5                            | 19                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M35 25 | 3,5                            | 25                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M35 95 | 3,5                            | 9,5                                         | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M39 13 | 3,9                            | 13                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M39 16 | 3,9                            | 16                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M39 19 | 3,9                            | 19                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M39 25 | 3,9                            | 25                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M39 32 | 3,9                            | 32                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M42 13 | 4,2                            | 13                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M42 16 | 4,2                            | 16                                          | PH    | A2 - stal<br>nierzewna | DIN 7504          | 1000                 | opak. |

| Catalogue | Index         | Ø d [mm]<br>Thread<br>diameter | l [mm]<br>Working<br>length of the<br>screw | Guide | Material grade          | Other<br>standard | Quantity per<br>pack | U.m.  |
|-----------|---------------|--------------------------------|---------------------------------------------|-------|-------------------------|-------------------|----------------------|-------|
| ●         | EZ75042M42 19 | 4,2                            | 19                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M42 22 | 4,2                            | 22                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M42 25 | 4,2                            | 25                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M42 32 | 4,2                            | 32                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M48 16 | 4,8                            | 16                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M48 19 | 4,8                            | 19                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M48 25 | 4,8                            | 25                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M48 32 | 4,8                            | 32                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M48 38 | 4,8                            | 38                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M48 45 | 4,8                            | 45                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M48 50 | 4,8                            | 50                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M48 60 | 4,8                            | 60                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M48 70 | 4,8                            | 70                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M48 75 | 4,8                            | 75                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M48 80 | 4,8                            | 80                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M48 90 | 4,8                            | 90                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M55 16 | 5,5                            | 16                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M55 19 | 5,5                            | 19                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75042M55 25 | 5,5                            | 25                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M55 32 | 5,5                            | 32                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M55 35 | 5,5                            | 35                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M55 38 | 5,5                            | 38                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 500                  | opak. |
| ●         | EZ75042M55 40 | 5,5                            | 40                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 200                  | opak. |
| ●         | EZ75042M55 45 | 5,5                            | 45                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 200                  | opak. |
| ●         | EZ75042M55 50 | 5,5                            | 50                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 200                  | opak. |
| ●         | EZ75042M55 60 | 5,5                            | 60                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 200                  | opak. |
| ●         | EZ75042M55 70 | 5,5                            | 70                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 200                  | opak. |
| ●         | EZ75042M55 80 | 5,5                            | 80                                          | PH    | A2 - stal<br>nierdzewna | DIN 7504          | 200                  | opak. |

| Catalogue | Index          | Ø d [mm]<br>Thread<br>diameter | l [mm]<br>Working<br>length of the<br>screw | Guide | Material grade            | Other<br>standard | Quantity per<br>pack | U.m.  |
|-----------|----------------|--------------------------------|---------------------------------------------|-------|---------------------------|-------------------|----------------------|-------|
| ●         | EZ75042M55 90  | 5,5                            | 90                                          | PH    | A2 - stal<br>nierzewna    | DIN 7504          | 200                  | opak. |
| ●         | EZ75042M55 100 | 5,5                            | 100                                         | PH    | A2 - stal<br>nierzewna    | DIN 7504          | 200                  | opak. |
| ●         | EZ75044M39 13  | 3,9                            | 13                                          | PH    | A4 - stal<br>kwasoodporna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75044M42 19  | 4,2                            | 19                                          | PH    | A4 - stal<br>kwasoodporna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75044M48 19  | 4,8                            | 19                                          | PH    | A4 - stal<br>kwasoodporna | DIN 7504          | 1000                 | opak. |
| ●         | EZ75044M48 22  | 4,8                            | 22                                          | PH    | A4 - stal<br>kwasoodporna | DIN 7504          | 1000                 | opak. |

Key: A2 - stainless steel, A4 - acid-resistant steel

Minimum order quantity: 1 pack

Net price per 1 pack

Any trade marks and/or company or product names used on this website belong to and/or are registered by their respective owners and are used solely for information purposes; this should not be construed as granting any licence or right to use them.

## Download

[Kat\\_GLOTECH\\_DIN 7504M PH.pdf](#)

## Related products

[GLOTECH - Self-drilling screws with hexagonal head - DIN 7504 K](#)

[GLOTECH - Self-tapping screws with flat-lens TORX head - DIN 7504 M.TX](#)

[GLOTECH - PH flat-conical head self-tapping screws - DIN 7504 O](#)

[GLOTECH - Self-tapping screws with conical-flat TORX head - DIN 7504 O.TX](#)

