



EZ14586

# GLOTECH - Self-tapping screws with a countersunk head and TORX socket - ISO 14586

New



## Features - benefits

GLOTECH TORX pan-head self-tapping screws are made from A2 (stainless steel) or, on request, from A4 (acid-resistant steel).  
Self-tapping screws with other technical specifications can be manufactured on request

## Application

self-tapping screw with TORX drive for joining metal components (sheet metal up to 0.5 mm thick)  
sheet metal screw for fastening metals to other materials  
sheet metal screw with a TORX drive, where the force is transmitted via the large surface area of the shank's sides  
used in the automotive industry, construction, interior fittings, upholstery, etc.  
used in many fields of application and across various industries

| Catalogue | Index         | Ø d [mm]<br>Thread<br>diameter | l [mm]<br>Working<br>length of self-<br>tapping<br>screw | Guide | Other<br>information | Material<br>grade      | Other<br>standard | Quantity per<br>pack | U.m.  |
|-----------|---------------|--------------------------------|----------------------------------------------------------|-------|----------------------|------------------------|-------------------|----------------------|-------|
| ●         | EZ14586239 16 | 3,9                            | 16                                                       | TX15  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586239 32 | 3,9                            | 32                                                       | TX15  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586239 50 | 3,9                            | 50                                                       | TX15  |                      | A2 - stal<br>nierzewna | DIN 7982          | 500                  | opak. |
| ○         | EZ14586239 65 | 3,9                            | 6,5                                                      | TX15  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586242 13 | 4,2                            | 13                                                       | TX20  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586242 16 | 4,2                            | 16                                                       | TX20  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586248 13 | 4,8                            | 13                                                       | TX25  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586248 16 | 4,8                            | 16                                                       | TX25  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586248 19 | 4,8                            | 19                                                       | TX25  |                      | A2 - stal<br>nierzewna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586248 25 | 4,8                            | 25                                                       | TX25  |                      | A2 - stal<br>nierzewna | DIN 7982          | 500                  | opak. |
| ●         | EZ14586248 32 | 4,8                            | 32                                                       | TX25  |                      | A2 - stal<br>nierzewna | DIN 7982          | 500                  | opak. |
| ●         | EZ14586248 38 | 4,8                            | 38                                                       | TX25  |                      | A2 - stal<br>nierzewna | DIN 7982          | 500                  | opak. |

| Catalogue | Index         | Ø d [mm]<br>Thread<br>diameter | l [mm]<br>Working<br>length of self-<br>tapping<br>screw | Guide | Other<br>information | Material<br>grade          | Other<br>standard | Quantity per<br>pack | U.m.  |
|-----------|---------------|--------------------------------|----------------------------------------------------------|-------|----------------------|----------------------------|-------------------|----------------------|-------|
| ●         | EZ14586248 45 | 4,8                            | 45                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586248 50 | 4,8                            | 50                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586248 60 | 4,8                            | 60                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586248 70 | 4,8                            | 70                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ○         | EZ14586248 80 | 4,8                            | 80                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586255 13 | 5,5                            | 13                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586255 16 | 5,5                            | 16                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 1000                 | opak. |
| ○         | EZ14586255 19 | 5,5                            | 19                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586255 25 | 5,5                            | 25                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 500                  | opak. |
| ●         | EZ14586255 32 | 5,5                            | 32                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 500                  | opak. |
| ●         | EZ14586255 38 | 5,5                            | 38                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 500                  | opak. |
| ●         | EZ14586255 45 | 5,5                            | 45                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586255 50 | 5,5                            | 50                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586255 60 | 5,5                            | 60                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ○         | EZ14586255 70 | 5,5                            | 70                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ○         | EZ14586255 80 | 5,5                            | 80                                                       | TX25  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586263 13 | 6,3                            | 13                                                       | TX30  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 500                  | opak. |
| ●         | EZ14586263 16 | 6,3                            | 16                                                       | TX30  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 500                  | opak. |
| ●         | EZ14586263 19 | 6,3                            | 19                                                       | TX30  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 500                  | opak. |
| ●         | EZ14586263 25 | 6,3                            | 25                                                       | TX30  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586263 32 | 6,3                            | 32                                                       | TX30  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586263 50 | 6,3                            | 50                                                       | TX30  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586263 60 | 6,3                            | 60                                                       | TX30  |                      | A2 - stal<br>nierzewna     | DIN 7982          | 200                  | opak. |
| ●         | EZ14586439 13 | 3,9                            | 13                                                       | TX15  |                      | A4 - stal kwa<br>soodporna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586442 25 | 4,2                            | 25                                                       | TX20  |                      | A4 - stal kwa<br>soodporna | DIN 7982          | 1000                 | opak. |
| ●         | EZ14586442 32 | 4,2                            | 32                                                       | TX20  |                      | A4 - stal kwa<br>soodporna | DIN 7982          | 500                  | opak. |
| ○         | EZ14586448 13 | 4,8                            | 13                                                       | TX25  |                      | A4 - stal kwa<br>soodporna | DIN 7982          | 1000                 | opak. |

| Catalogue | Index         | Ø d [mm]<br>Thread<br>diameter | l [mm]<br>Working<br>length of self-<br>tapping<br>screw | Guide | Other<br>information | Material<br>grade          | Other<br>standard | Quantity per<br>pack | U.m.  |
|-----------|---------------|--------------------------------|----------------------------------------------------------|-------|----------------------|----------------------------|-------------------|----------------------|-------|
| o         | EZ14586448 16 | 4,8                            | 16                                                       | TX25  |                      | A4 - stal kwa<br>soodporna | DIN 7982          | 1000                 | opak. |

Key: A2 - stainless steel, A4 - acid-resistant steel

Minimum order quantity: 1 pack

Net price per 1 pack

Any trade marks and/or company or product names used on this website belong to and/or are registered by their respective owners and are used solely for information purposes; this should not be construed as granting any licence or right to use them.

## Download

[Kat\\_GLOTECH\\_ISO 14586 - DIN 7982 TORX.pdf](#)

## Related products

[GLOTECH - Hexagon head sheet metal screws - DIN 7976](#)



[GLOTECH - Flat-lenticular-head self-tapping screws with PH socket - DIN 7981](#)



[GLOTECH - Flat-lens head self-tapping screws with TORX drive - ISO 14585](#)



[GLOTECH - Flat-conical head self-tapping screws with PH drive - DIN 7982 C-H](#)



[GLOTECH - Self-tapping screws with a cylindrical head, head to DIN 912 - hexagonal socket - Item No. 9051](#)

