



EZ14586

GLOTECH - Self-tapping screws with a countersunk head and TORX socket - ISO 14586

New



Features - benefits

GLOTECH TORX pan-head self-tapping screws are made from A2 (stainless steel) or, on request, from A4 (acid-resistant steel).
Self-tapping screws with other technical specifications can be manufactured on request

Application

self-tapping screw with TORX drive for joining metal components (sheet metal up to 0.5 mm thick)
sheet metal screw for fastening metals to other materials
sheet metal screw with a TORX drive, where the force is transmitted via the large surface area of the shank's sides
used in the automotive industry, construction, interior fittings, upholstery, etc.
used in many fields of application and across various industries

Catalogue	Index	Ø d [mm] Thread diameter	l [mm] Working length of self- tapping screw	Guide	Other information	Material grade	Other standard	Quantity per pack	U.m.
●	EZ14586239 16	3,9	16	TX15		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586239 32	3,9	32	TX15		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586239 50	3,9	50	TX15		A2 - stal nierzewna	DIN 7982	500	opak.
○	EZ14586239 65	3,9	6,5	TX15		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586242 13	4,2	13	TX20		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586242 16	4,2	16	TX20		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586248 13	4,8	13	TX25		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586248 16	4,8	16	TX25		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586248 19	4,8	19	TX25		A2 - stal nierzewna	DIN 7982	1000	opak.
●	EZ14586248 25	4,8	25	TX25		A2 - stal nierzewna	DIN 7982	500	opak.
●	EZ14586248 32	4,8	32	TX25		A2 - stal nierzewna	DIN 7982	500	opak.
●	EZ14586248 38	4,8	38	TX25		A2 - stal nierzewna	DIN 7982	500	opak.

Catalogue	Index	Ø d [mm] Thread diameter	l [mm] Working length of self- tapping screw	Guide	Other information	Material grade	Other standard	Quantity per pack	U.m.
●	EZ14586248 45	4,8	45	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586248 50	4,8	50	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586248 60	4,8	60	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586248 70	4,8	70	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
○	EZ14586248 80	4,8	80	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586255 13	5,5	13	TX25		A2 - stal nierdzewna	DIN 7982	1000	opak.
●	EZ14586255 16	5,5	16	TX25		A2 - stal nierdzewna	DIN 7982	1000	opak.
○	EZ14586255 19	5,5	19	TX25		A2 - stal nierdzewna	DIN 7982	1000	opak.
●	EZ14586255 25	5,5	25	TX25		A2 - stal nierdzewna	DIN 7982	500	opak.
●	EZ14586255 32	5,5	32	TX25		A2 - stal nierdzewna	DIN 7982	500	opak.
●	EZ14586255 38	5,5	38	TX25		A2 - stal nierdzewna	DIN 7982	500	opak.
●	EZ14586255 45	5,5	45	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586255 50	5,5	50	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586255 60	5,5	60	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
○	EZ14586255 70	5,5	70	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
○	EZ14586255 80	5,5	80	TX25		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586263 13	6,3	13	TX30		A2 - stal nierdzewna	DIN 7982	500	opak.
●	EZ14586263 16	6,3	16	TX30		A2 - stal nierdzewna	DIN 7982	500	opak.
●	EZ14586263 19	6,3	19	TX30		A2 - stal nierdzewna	DIN 7982	500	opak.
●	EZ14586263 25	6,3	25	TX30		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586263 32	6,3	32	TX30		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586263 50	6,3	50	TX30		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586263 60	6,3	60	TX30		A2 - stal nierdzewna	DIN 7982	200	opak.
●	EZ14586439 13	3,9	13	TX15		A4 - stal kwa soodporna	DIN 7982	1000	opak.
●	EZ14586442 25	4,2	25	TX20		A4 - stal kwa soodporna	DIN 7982	1000	opak.
●	EZ14586442 32	4,2	32	TX20		A4 - stal kwa soodporna	DIN 7982	500	opak.
○	EZ14586448 13	4,8	13	TX25		A4 - stal kwa soodporna	DIN 7982	1000	opak.

Catalogue	Index	Ø d [mm] Thread diameter	l [mm] Working length of self- tapping screw	Guide	Other information	Material grade	Other standard	Quantity per pack	U.m.
o	EZ14586448 16	4,8	16	TX25		A4 - stal kwa soodporna	DIN 7982	1000	opak.

Key: A2 - stainless steel, A4 - acid-resistant steel
Minimum order quantity: 1 pack
Net price per 1 pack
Any trade marks and/or company or product names used on this website belong to and/or are registered by their respective owners and are used solely for information purposes; this should not be construed as granting any licence or right to use them.

Download

[Kat_GLOTECH_ISO 14586 - DIN 7982 TORX.pdf](#)

Related products

- [GLOTECH - Hexagon head sheet metal screws - DIN 7976](#)
- [GLOTECH - Flat-lenticular-head self-tapping screws with PH socket - DIN 7981](#)
- [GLOTECH - Flat-lens head self-tapping screws with TORX drive - ISO 14585](#)
- [GLOTECH - Flat-conical head self-tapping screws with PH drive - DIN 7982 C-H](#)



[GLOTECH - Self-tapping screws with a cylindrical head, head to DIN 912 - hexagonal socket - Item No. 9051](#)

