



PT110

Saw blades LA for soft wood ripping



Features - benefits

- » saws made from high quality, thermally improved steel
- » laser cutting technology results in very precise disc execution
- » due to heavy and unstable working conditions saw blades are also made with special heat compensating grooves and special slots
- » compensation slots ensures proper disc cooling and therefore increase its rigidity
- » regular and symmetric teeth setting - standard saw blades made in sharpened and set version

Application

- » dedicated to soft wood ripping (cutting wood along the grain)
- » used mainly on popular circular saws and other stationary machines

Catalogue	Index	Ø D [mm] Outer diameter	Ø d [mm] Inner diameter	S [mm] Disc thickness	Z Teeth number	Teeth geometry	U.m.
●	PT110-0115-0001	0115	22,2	1,0	36	LA	szt.
●	PT110-0125-0005	0125	22,2	1,0	36	LA	szt.
●	PT110-0125-0006	0125	22,2	1,2	36	LA	szt.
○	PT110-0160-0003	0160	20	1,6	36	LA	szt.
●	PT110-0180-0001	0180	30	1,6	36	LA	szt.
●	PT110-0200-0001	0200	30	1,6	36	LA	szt.
●	PT110-0200-0002	0200	30	2,0	36	LA	szt.
●	PT110-0250-0001	0250	30	1,6	36	LA	szt.
●	PT110-0250-0002	0250	30	2,0	36	LA	szt.
●	PT110-0250-0003	0250	30	2,5	36	LA	szt.
●	PT110-0300-0001	0300	30	2,0	30	LA	szt.
●	PT110-0300-0002	0300	30	2,5	30	LA	szt.
●	PT110-0300-0003	0300	30	3,2	30	LA	szt.
●	PT110-0315-0001	0315	30	2,0	30	LA	szt.
●	PT110-0315-0004	0315	30	2,5	30	LA	szt.
●	PT110-0315-0002	0315	30	3,2	30	LA	szt.
●	PT110-0350-0001	0350	30	2,0	36	LA	szt.
●	PT110-0350-0002	0350	30	2,5	36	LA	szt.
●	PT110-0350-0003	0350	30	3,2	36	LA	szt.
●	PT110-0350-0009	0350	30	3,5	36	LA	szt.
●	PT110-0350-0005	0350	90	3,5	24	LA	szt.

Catalogue	Index	Ø D [mm] Outer diameter	Ø d [mm] Inner diameter	S [mm] Disc thickness	Z Teeth number	Teeth geometry	U.m.
●	PT110-0400-0001	0400	30	2,0	36	LA	szt.
●	PT110-0400-0002	0400	30	2,5	36	LA	szt.
●	PT110-0400-0016	0400	30	2,8	36	LA	szt.
●	PT110-0400-0006	0400	30	3,2	24	LA	szt.
●	PT110-0400-0003	0400	30	3,2	36	LA	szt.
●	PT110-0400-0004	0400	30	3,5	36	LA	szt.
●	PT110-0450-0001	0450	30	2,5	36	LA	szt.
●	PT110-0450-0004	0450	30	3,5	24	LA	szt.
●	PT110-0450-0003	0450	30	3,2	36	LA	szt.
●	PT110-0450-0005	0450	30	3,5	36	LA	szt.
●	PT110-0500-0001	0500	30	2,5	36	LA	szt.
●	PT110-0500-0004	0500	30	3,2	36	LA	szt.
●	PT110-0500-0005	0500	30	3,5	36	LA	szt.
●	PT110-0550-0001	0550	30	3,2	48	LA	szt.
●	PT110-0550-0002	0550	30	3,5	48	LA	szt.
●	PT110-0630-0003	0630	40	3,2	36	LA	szt.
●	PT110-0630-0001	0630	40	3,5	36	LA	szt.
●	PT110-0630-0002	0630	40	4,0	36	LA	szt.
●	PT110-0710-0001	0710	40	4,0	36	LA	szt.
●	PT110-0800-0002	0800	40	4,5	36	LA	szt.
○	PT110-0900-0003	0900	40	5,0	56	LA	szt.
○	PT110-1000-0003	1000	40	5,0	56	LA	szt.

Download

[TechInfo_PT_eng.pdf](#)
[UserManual_PT_GLOBUS_eng.pdf](#)

Related products

[Saw blades WA for soft wood ripping](#)

[Saw blades KB for soft and hard wood cross cutting](#)

[GO Cleaner - cleaning fluid for tools and machines](#)
