# PT110 Saw blades LA for soft wood ripping



## Features - benefits

- saws made from high quality, thermally improved steel
- laser cutting technology results in very precise disc execution
- due to heavy and unstable working conditions saw blades are also made with special heat compensating grooves and special slots
- compensation slots ensures proper disc cooling and therefore increase its rigidity
- regular and symmetric teeth setting - standard saw blades made in sharpened and set version

## Application

- dedicated to soft wood ripping (cutting wood along the grain)
- used mainly on popular circular saws and other stationary machines

| Catalogue | Index | ∅ D [mm] Outer diameter | ∅ d [mm] Inner diameter | S [mm] Disc thickness | Z Teeth number | Teeth geometry | U.m. |
|---|---|---|---|---|---|---|---|
| ● | PT110-0115-0001 | 0115 | 22,2 | 1,0 | 36 | LA | szt. |
| ● | PT110-0125-0005 | 0125 | 22,2 | 1,0 | 36 | LA | szt. |
| ● | PT110-0125-0006 | 0125 | 22,2 | 1,2 | 36 | LA | szt. |
| ○ | PT110-0160-0003 | 0160 | 20 | 1,6 | 36 | LA | szt. |
| ● | PT110-0180-0001 | 0180 | 30 | 1,6 | 36 | LA | szt. |
| ● | PT110-0200-0001 | 0200 | 30 | 1,6 | 36 | LA | szt. |
| ● | PT110-0200-0002 | 0200 | 30 | 2,0 | 36 | LA | szt. |
| ● | PT110-0250-0001 | 0250 | 30 | 1,6 | 36 | LA | szt. |
| ● | PT110-0250-0002 | 0250 | 30 | 2,0 | 36 | LA | szt. |
| ● | PT110-0250-0003 | 0250 | 30 | 2,5 | 36 | LA | szt. |
| ● | PT110-0300-0001 | 0300 | 30 | 2,0 | 30 | LA | szt. |
| ● | PT110-0300-0002 | 0300 | 30 | 2,5 | 30 | LA | szt. |
| ● | PT110-0300-0003 | 0300 | 30 | 3,2 | 30 | LA | szt. |
| ● | PT110-0315-0001 | 0315 | 30 | 2,0 | 30 | LA | szt. |
| ● | PT110-0315-0004 | 0315 | 30 | 2,5 | 30 | LA | szt. |
| ● | PT110-0315-0002 | 0315 | 30 | 3,2 | 30 | LA | szt. |
| ● | PT110-0350-0001 | 0350 | 30 | 2,0 | 36 | LA | szt. |
| ● | PT110-0350-0002 | 0350 | 30 | 2,5 | 36 | LA | szt. |
| ● | PT110-0350-0003 | 0350 | 30 | 3,2 | 36 | LA | szt. |
| ● | PT110-0350-0009 | 0350 | 30 | 3,5 | 36 | LA | szt. |
| ● | PT110-0350-0005 | 0350 | 90 | 3,5 | 24 | LA | szt. |

| Catalogue | Index | ∅ D [mm] Outer diameter | ∅ d [mm] Inner diameter | S [mm] Disc thickness | Z Teeth number | Teeth geometry | U.m. |
|---|---|---|---|---|---|---|---|
| ● | PT110-0400-0001 | 0400 | 30 | 2,0 | 36 | LA | szt. |
| ● | PT110-0400-0002 | 0400 | 30 | 2,5 | 36 | LA | szt. |
| ● | PT110-0400-0016 | 0400 | 30 | 2,8 | 36 | LA | szt. |
| ● | PT110-0400-0006 | 0400 | 30 | 3,2 | 24 | LA | szt. |
| ● | PT110-0400-0003 | 0400 | 30 | 3,2 | 36 | LA | szt. |
| ● | PT110-0400-0004 | 0400 | 30 | 3,5 | 36 | LA | szt. |
| ● | PT110-0450-0001 | 0450 | 30 | 2,5 | 36 | LA | szt. |
| ● | PT110-0450-0004 | 0450 | 30 | 3,5 | 24 | LA | szt. |
| ● | PT110-0450-0003 | 0450 | 30 | 3,2 | 36 | LA | szt. |
| ● | PT110-0450-0005 | 0450 | 30 | 3,5 | 36 | LA | szt. |
| ● | PT110-0500-0001 | 0500 | 30 | 2,5 | 36 | LA | szt. |
| ● | PT110-0500-0004 | 0500 | 30 | 3,2 | 36 | LA | szt. |
| ● | PT110-0500-0005 | 0500 | 30 | 3,5 | 36 | LA | szt. |
| ● | PT110-0550-0001 | 0550 | 30 | 3,2 | 48 | LA | szt. |
| ● | PT110-0550-0002 | 0550 | 30 | 3,5 | 48 | LA | szt. |
| ● | PT110-0630-0003 | 0630 | 40 | 3,2 | 36 | LA | szt. |
| ● | PT110-0630-0001 | 0630 | 40 | 3,5 | 36 | LA | szt. |
| ● | PT110-0630-0002 | 0630 | 40 | 4,0 | 36 | LA | szt. |
| ● | PT110-0710-0001 | 0710 | 40 | 4,0 | 36 | LA | szt. |
| ● | PT110-0800-0002 | 0800 | 40 | 4,5 | 36 | LA | szt. |
| ○ | PT110-0900-0003 | 0900 | 40 | 5,0 | 56 | LA | szt. |
| ○ | PT110-1000-0003 | 1000 | 40 | 5,0 | 56 | LA | szt. |

## Download

TechInfo_PT_eng.pdf
UserManual_PT_GLOBUS_eng.pdf

## Related products

Saw blades WA for soft wood ripping

Saw blades KB for soft and hard wood cross cutting

GO Cleaner - cleaning fluid for tools and machines